

# The Original Giles Tactical Sling

Installation procedure for:

## Military M1 Carbine with fixed wood stock

### Attaching the Front Sling Adapter

Pass the sling's 1" front strap through carbine's front swivel, then back through the tri-glide buckle. Loop it back over the top of the buckle and feed back through towards the front. This extra pass-through offers additional security.




### Attaching the Rear Sling Adapter

On the left side of the weapon, pass the sling's 1" rear adapter strap through the oiler slot, from front to back WHILE THE OILER IS IN PLACE. There should be no need to remove the extremely tight oiler. Pull the tip of the strap all the way through the slot, then thread it through the tri-glide buckle towards the front. Loop it back over the top of the buckle and feed back through towards the rear. This extra pass-through offers additional security.



Rear, opposite side



Rear



### WARNING:

Mishandling of firearms may cause serious injury or death. Before practicing with your Original Giles Tactical Sling™ make sure your weapon is unloaded and pointed in a safe direction. When handling the firearm, make sure your index finger remains straight along the weapon's frame and not in contact with the trigger! **Do not touch the trigger until your sights are on the target and you are ready to fire.** If the sling interferes with the safe operation or handling of the weapon, discontinue use. For further safety considerations, consult the owner's manual of your weapon and seek professional assistance.

Complete



© 2011 All rights reserved.  
Reproduction in whole or in part is prohibited.

Wilderness Tactical Products, LLC • Wilderness Plaza • 1608 W. Hatcher Rd. • Phoenix, AZ 85021  
www.thewilderness.com • Call for a dealer near you! Questions/inquiries: 602/242-4945  
Toll free order line: 1-800/775-5650 • Fax line: 602/242-8260